



TECHNICAL SERVICE BULLETIN

POLYCHEM 7718-B-75

POLYCHEM 7718 is a short oil coconut oil alkyd.

<u>CHARACTERISTIC</u>	<u>SPECIFICATIONS</u>
PERCENT NON-VOLATILE	74 - 76
VISCOSITY, G-H	W - Y
ACID NUMBER (NVM)	15 - 25
GARDNER COLOR	4 Max
POUNDS PER GALLON	8.8 +/- 0.1
SOLVENT	n-BA/Ethanol
OIL	Coconut
REDUCED VISCOSITY	H - L
REDUCED NVM	65
REDUCTION SOLVENT	n-BA
CLARITY	10 MAX
BROOKFIELD, 20 C	1,700 – 2,700 #3 @ 10rpm

SUGGESTED USES:

This product can be used in acid catalyzed wood conversion varnishes.
It may also be cross-linked with amino resins.

DRIER RECOMMENDATIONS (% Metal on total binder solids):

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that all workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.