

<b>POLYCHEM 6502-100</b>
--------------------------

**Polychem 6502-100 (Z2428)**

Polychem 6502-100 is an pure long oil alkyd formulated especially for the modification of latex house paints or other exterior latex coating applications where chalk binding, flexibility, and adhesion are necessary to augment the properties of a latex system. The modification level is typically 25% based upon total resin solids. This product is HAP-free.

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	99.5
Viscosity, G-H	W-Y
Acid Number	10
Gardner Color	10 Maximum
Weight Per Gallon	8.35 ± 0.1
Solvent	?
Modifier	?
Oil	Linseed Oil
Reduced Viscosity	B-D
Reduced NVM	70
Reduction Solvent	Mineral Spirits, Low Aromatic
Clarity	CLEAR TO SLIGHTLY HAZY
SUGGESTED USES	
(not specified)	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Cobalt      0.03% Manganese    0.03% Zirconium    0.25%	

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES