

POLYCHEM 7478-X-75

Polychem 7478-X-75 (Z8066)

Polychem 7478-X-75 is an phenolic modified alkyd supplied at 75% solids in xylene. Excellent choice for specialty coatings, especially non-lifting primers.

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	75
Viscosity, G-H	Z4-Z6
Acid Number	12 to 24
Gardner Color	15 Maximum
Weight Per Gallon	8.65 ± 0.1
Solvent	Xylene
Modifier	Phenolic
Oil	Linseed Oil/TUNG Oil/Tall Oil Fatty Acid
Reduced Viscosity	N-Q
Reduced NVM	60
Reduction Solvent	Xylene
Clarity	CLEAR TO SLIGHTLY HAZY
SUGGESTED USES	
Industrial primers	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Cobalt 0.08%Calcium 0.20%Zirconium 0.30%Dri RX 0.20%	

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES