

POLYCHEM 7519-B-70

Polychem 7519-B-70 (Z8126)

Polychem 7519-B-70 is an styrene/acrylic modified alkyd designed for air dry, force dry, or bake finishes providing a good degree of flexibility and good projected durability / color retention. This product is low-HAP and can be formulated into HAP-free coatings (below 1% HAP).

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	70
Viscosity, G-H	W-Z
Acid Number	14
Gardner Color	5 Maximum
Weight Per Gallon	8.4 ± 0.1
Solvent	BLEND
Modifier	ACR
Oil	Soybean Oil/Sunflower Oil
Reduced Viscosity	E-G
Reduced NVM	60
Reduction Solvent	METHYL n-PROPYL KETONE MPK
Clarity	CLEAR TO SLIGHTLY HAZY
SUGGESTED USES	
Farm implements / equipmentMetal product finishesBake enamels	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Cobalt 0.03%Zirconium 0.30%Calcium 0.03%	

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES