

POLYCHEM 7563-V-60

Polychem 7563-V-60 (Z0777)

Polychem 7563-V-60 is an vinyl toluene copolymer designed for use in primers, enamels, aerosols, and sanding sealers where lacquer type dry is required. This product is low-HAP and can be formulated into HAP-free coatings (below 1% HAP).

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	60
Viscosity, G-H	Y-Z1
Acid Number	4
Gardner Color	5 Maximum
Weight Per Gallon	7.4 ± 0.1
Solvent	VM&P
Modifier	VT
Oil	Linseed Oil
Reduced Viscosity	C-F
Reduced NVM	40
Reduction Solvent	VM&P
Clarity	CLEAR TO SLIGHTLY HAZY
SUGGESTED USES	
Equipment enamelsFloor sealers	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Cobalt	0.05%
Manganese	0.03%
Zirconium	0.50%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES