

<b>POLYCHEM 7687-OX-60</b>
----------------------------

Polychem 7687-OX-60 (Z8978)

Polychem 7687-OX-60 is an premium siliconized alkyd designed to produce durable high gloss air dry finishes. Reduced in Oxsol 100 and can be formulated into a HAP-free coating.

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	60
Viscosity, G-H	V-Y
Acid Number	12
Gardner Color	7 Maximum
Weight Per Gallon	9.95 ± 0.1
Solvent	Oxsol 100
Modifier	SILICONE
Oil	Soybean Oil
Reduced Viscosity	?
Reduced NVM	?
Reduction Solvent	
Clarity	10 MAX
SUGGESTED USES	
Transportation equipment enamelsExterior maintenance coatingsOutdoor signs	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Cobalt	0.04%
Manganese	0.04%
Calcium	0.05%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES