

POLYCHEM G2510-MS16-50

Polychem G2510-MS16-50 (Z2039)

Polychem G2510-MS16-50 is an glyptal medium oil alkyd. It is a general purpose vehicle for brushing or spraying enamels and primers.

CHARACTERISTICS	SPECIFICATIONS			
Percent Non Volatile	50			
Viscosity, G-H	Z-Z2			
Acid Number	10			
Gardner Color	7 Maximum			
Weight Per Gallon	7.65 ± 0.1			
Solvent	MS-16			
Modifier	?			
Oil	Soybean Oil			
Reduced Viscosity	G-J			
Reduced NVM	40			
Reduction Solvent	MS-16			
Clarity	10 Max			
SUGGESTED USES				
Used for lighter colors or low bake applications, and for dipping enamels.				
DRIER RECOMMENDATIONS (% metal on total binder solids)				
Air Dry: 25 C, 50% RH, 0.075 mm Wet	Touch Dry	Tack Free	4-6 hrs.	
HardDriers	Cobalt	0.04%	Calcium	0.1%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES