

<b>POLYCHEM G7589-100</b>
---------------------------

**Polychem G7589-100 (Z2075)**

Polychem G7589-100 is an glyptal long oil alkyd. It has quick surface dry which makes it less prone to the incorporation of dirt or other contaminants.

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	99.5
Viscosity, G-H	Z2-Z4
Acid Number	10
Gardner Color	9 Maximum
Weight Per Gallon	8.35 ± 0.1
Solvent	?
Modifier	?
Oil	Soybean Oil
Reduced Viscosity	?
Reduced NVM	?
Reduction Solvent	
Clarity	CLEAR
SUGGESTED USES	
Used as a grinding vehicle to obtain good initial gloss in house paints because of its very good wetting properties.	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Air Dry: 25 C, 50% RH, 0.075 mm Wet	Touch Dry Tack FreeDriers: Cobalt
0.04% Calcium 0.1% Zirconium	0.1%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES