

POLYCHEM G7773-MS16-50

Polychem G7773-MS16-50 (Z2138)

Polychem G7773-MS16-50 is an medium oil Soya-Tung alkyd. It offers excellent exterior durability. It also has very good gloss and color retention.

CHARACTERISTICS	SPECIFICATIONS
Percent Non Volatile	50
Viscosity, G-H	Z3-Z5
Acid Number	12
Gardner Color	6 Maximum
Weight Per Gallon	7.65 ± 0.1
Solvent	MS-16
Modifier	?
Oil	Soya/Tung Oil
Reduced Viscosity	Q-U
Reduced NVM	40
Reduction Solvent	MS16
Clarity	CLEAR
SUGGESTED USES	
Used for farm implement and industrial finishing enamels	
DRIER RECOMMENDATIONS (% metal on total binder solids)	
Air Dry:	25 C, 50% RH, 0.075 mm Wet
Touch Dry	Tack Free
3-4 Hours	
Hard	6 Hours
Driers:	Cobalt
0.05%	Calcium
The information and specifications stated here are for the material currently offered, are	

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES