

POLYCHEM G7790-MS7-60

Polychem G7790-MS7-60 (Z2152)

Polychem G7790-MS7-60 is an product designed to be used in a low odor architectural system. It also provides excellent gloss and color retention.

HARACTERISTICS		SPECIFICATIONS			
Percent Non Volatile		60			
Viscosity, G-H		Z3-Z4			
Acid Number		10			
Gardner Color		7 Maximum			
Weight Per Gallon		7.83 ± 0.1			
Solvent		MS-7			
Modifier		?			
Oil		Soybean Oil			
Reduced Viscosity		S-V			
Reduced NVM		50			
Reduction Solvent		MS7			
Clarity		Clear			
SUGGESTED USES					
Low odor architectural coating.					
DRIER RECOMMENDATIONS (% metal on to	otal binder soli	ds)			
Air Dry: 25C, 50% RH, 0.075 mm Wet	Touch Dry		Tack Free	5 ? 6 HoursDriers:	Cobalt
0.04% Calcium 0.10%					

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES